

Cavity 腔型	GP100C 粗	GP100M 中	GP100MF 中细	GP100EF 超细	GP100SM 标中
Feed opening size 给料尺寸 (mm)	150	130	100	400	200
Max feeding size 最大给料尺寸 (mm)	120	105	85	32	170
Weight 总重(kg)	5700	5700	5700	5700	7350

The choice of motor: the 16 stroke, suggest use 75kW motor, 20-25stroke, suggest use 90kW. 电机选择: 16冲程选用75KW电机。20和25冲程选用90KW电机

Model 型号	Cavity 腔型	Max feeding size 最大给料尺寸 (mm)	Discharge opening排料口 (mm) (CSS) Capacity对应产量 (t/h)											
			5mm	6mm	7mm	11mm	12mm	13mm	15mm	17mm	18mm	19mm	22mm	24mm
DP100	C	120						65-70	70-85	75-100	75-105	80-110	85-120	90-100
	M	105				55-80	60-85		65-90	65-95	70-100	75-100		
	MF	85			45-50	50-75		55-80	60-85		65-90	65-80		
	EF	32	35-40	40-55	40-60	45-70	55-75		60-75	65				
Model 型号	Cavity 腔型	Max feeding size 最大给料尺寸 (mm)	Discharge opening排料口 (mm) (CSS) Capacity对应产量 (t/h)											
DP100S	SM	170	20mm		25mm		30mm		35mm		40mm		45mm	
			85-90	105-145	125-175	145-200	165-215	55-80						

DP430, DP430S, DP440, DP440S, DP660, DP660S Single-cylinder hydraulic cone crusher Technical data
DP430, DP430S, DP440, DP440S, DP660, DP660S圆锥破碎机技术参数

Model 型号	Cavity 腔型	Max feeding size 最大给料尺寸 (mm)	Discharge opening排料口 (mm) (CSS) Capacity对应产量 (t/h)											
			25mm	29mm	32mm	35mm	38mm	41mm	44mm	48mm	51mm	54mm		
DP440S	EC	450					267	282-353	298-446	313-563	334-601	390-524	365-456	
	C	400		225	239-299	254-381	269-484	284-511	298-448	318-398	333			
	MC	300	195	214-267	228-342	242-435	256-461	270-486	284-426	303-378	317			
Model 型号	Cavity 腔型	Max feeding size 最大给料尺寸 (mm)	Discharge opening排料口 (mm) (CSS) Capacity对应产量 (t/h)											
DP440	EC	215	8mm	10mm	13mm	16mm	19mm	22mm	25mm	32mm	38mm	44mm		
			114-200	122-276	131-294	139-313	159-357	175-395	192-384					
	C	175			101	109-218	117-292	125-312	133-332	151-378	167-335	183-229		
			97-122	105-262	113-282	120-301	128-320	146-328	161-242					
	M	110			117-187	126-278	136-298	145-318	154-339	175-281	194			
	MF	85		114	124-227	134-245	144-263	153-281	163-299	186-248				
	F	70	90-135	96-176	104-191	112-206	120-221	129-236	137-251	156-208				
	EF	38	100-125t/h, 其中80%小于6mm-7.5mm											

Model 型号	DP430S	DP430	DP440S	DP440	DP660S	DP660
Weight 总重(kg)	9200	12000	19300	14300	35700	26800
Power 功率(kw)	132	132	220	220	315	315

Model 型号	Cavity 腔型	Max feeding size 最大给料尺寸 (mm)	Discharge opening排料口 (mm) (CSS) Capacity对应产量 (t/h)										
			19mm	22mm	25mm	29mm	32mm	35mm	38mm	41mm	44mm	48mm	51mm
DP430S	EC	360			126	138-173	147-230	156-293	165-310	174-327	183-344	196-306	205-256
	C	300		108	116-145	127-199	135-254	144-270	152-285	161-301	196-264	108	
	MC	235	91	98-123	106-166	116-218	124-232	131-146	139-261	147-275	154-241	165	

Model 型号	Cavity 腔型	Max feeding size 最大给料尺寸 (mm)	Discharge opening排料口 (mm) (CSS) Capacity对应产量 (t/h)										
			6mm	8mm	10mm	13mm	16mm	19mm	22mm	25mm	32mm	38mm	
DP430	EC	185				69-108	75-150	80-161	86-171	91-182	104-208	115-208	
	C	145				66-131	71-142	76-152	81-162	86-173	98-197	109-150	
	MC	115			57	62-140	67-151	72-162	77-173	82-184	93-145		
	M	90			64-84	69-131	75-142	80-152	86-162	91-154	104		
	MF	75		61	65-106	70-115	76-124	81-126	87-114	92			
	F	50	48-78	51-83	54-88	59-96	63-103	68-105	72-95	77			
	EF	35	70-90t/h, 其中80%小于5mm-5.6mm										

Model 型号	Cavity 腔型	Max feeding size 最大给料尺寸 (mm)	Discharge opening排料口 (mm) (CSS) Capacity对应产量 (t/h)											
			38mm	41mm	44mm	48mm	51mm	54mm	60mm	64mm	70mm	76mm	83mm	
DP660S	EC	560			349	368-460	392-588	410-718	428-856	465-529	489-978	525-1050	562-983	604
	C	500	318	336-420	353-618	376-753	394-788	411-823	446-892	469-822	504-631			

Model 型号	Cavity 腔型	Max feeding size 最大给料尺寸 (mm)	Discharge opening排料口 (mm) (CSS) Capacity对应产量 (t/h)										
			13mm	16mm	19mm	22mm	25mm	32mm	38mm	44mm	51mm		
DP660	EC	270			177	190-338	203-436	216-464	246-547	272-605	298-662	328-511	
	C	235			174-194	187-374	200-488	212-519	242-592	268-654	293-521	323-359	
	CX	215			171-190	184-367	196-480	209-510	238-582	263-643	288-512	317-353	
	MC	175			162-253	174-426	186-455	198-484	226-552	249-499	273-364		
	M	135			197-295	211-440	226-470	240-500	274-502	302-403			
	MF	115	192	207-369	222-396	237-423	252-450	287-451	318-363				
	F	90	195-304	210-328	225-352	241-376	256-400	292-401	323				
	EF	65	211-293	227-316	244-298	261-290							